



Parameter Classification	Parameter	Unit	MA900II/260		
			A	B	C
INJECTION UNIT	Screw Diameter	mm	32	36	40
	Screw L/D Ratio	L/D	22.5	20	18
	Shot Size (Theoretical)	cm³	121	153	188
	Injection Weight (PS)	g	110	139	171
	Injection Rate	g/s	77	98	121
	Injection Pressure	Mpa	219	173	140
	Plasticizing Capacity(ps)	g/s	10.1	13.3	16.1
	Screw Speed	rpm	0-230		
CLAMPING UNIT	Clamp Tonnage	KN	900		
	Toggle Stroke	mm	320		
	Space Between Tie Bars	mm	360×360		
	Max.Mold Height	mm	380		
	Min. Mold Height	mm	150		
	Ejector Stroke	mm	100		
	Ejector Tonnage	KN	33		
	Max. Pump Pressure	Mpa	16		
OTHERS	Pump Motor Power	Kw	11		
	Heater Power	Kw	6.3		
	Machine Dimension(L×W×H)	m	4.4×1.13×1.91		
	Machine Weight	t	3.5		
	Hopper Capacity	Kg	25		
	Oil Tank Capacity	L	160		
Description	Suitable Products: - Daily household plastics: small & medium storage boxes, kitchen & bathroom accessories, cosmetic containers, daily-use plastic housings - Electronic components: small-medium appliance shells, electrical enclosures, switch parts and connector components - Auto plastic parts: small automotive interior trims, plastic brackets, protective covers and fastening parts - Packaging articles: small-size packaging containers, caps, closures and general miniature industrial plastic fittings				