



Parameter Classification	Parameter	Unit	A	B	C
INJECTION UNIT	Shotvolume	cm ³	834.1	978.9	1135.3
	Shotweight(PS)	g	767.3	900.6	1044.4
	Shotweight(PS)	oz	27.1	31.8	36.9
	Screw diameter	mm	60	65	70
	Injection pressure	MPa	217	184.9	159.5
	Injection rate	g/s	237.5	278.7	323.2
	Screw L:D ratio	L/D	22.6:1	20.9:1	19.4:1
	Plasticizing capacity	g/s	43.5	55.2	67.2
	Max. injection speed	mm/s		91.3	
	Screw stroke	mm		295	
	Screw speed (stainless)	r/min		0-195	
CLAMPING UNIT	Clamping force	kN		3200	
	Opening stroke	mm		580	
	Space between tiebars	mm×mm		670×670	
	Max. Daylight	mm		1240	
	Mold thickness (Min. Max)	mm		220-660	
	Ejector stroke	mm		170	
	Ejector number			13	
	Ejector force	kN		77	
POWER UNIT	Hydraulic system pressure	MPa		17.5	
	Pump motor power	kW		35.2	
	Heater power	kW		22.9	
	Number of temp control zones			5	
GENERAL UNIT	Dry cycle time	s		3.4	
	Oil tank capacity	L		326	
	Machined dimensions (L×W×H)	m×m×m		6.63×1.66×2.21	
	Design Weight	kg		9200	
Description	Suitable Products: -Daily plastics: medium-large daily-use articles, large household storage containers, thick-wall daily necessities, medium-large commodity shells -Auto parts: medium-large auto interior-exterior trim parts, auto decorative accessories, vehicle medium-heavy load structural moldings -Electronics & Industrial: medium-large electronic housings, heavy-duty plastic fittings, large-scale engineering plastic components -Home appliance & Packaging: medium-large appliance outer shells, large-volume packaging goods, mid-heavy weight consumer plastic articles				